

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more](#) ▼

[Web History](#) | [Search settings](#) | [Sign in](#)


About 3,250,000 results (0.26 seconds)

[Advanced search](#)**Everything**

More

[Show search tools](#)**HTTP/1.1: Header Field Definitions**

part of Hypertext Transfer **Protocol** -- HTTP/1.1 If the request would, without the **If-Match header** field, result in anything ... to use the exact date **string** received in a previous Last-Modified **header** field whenever possible. ...

www.w3.org/Protocols/rfc2616/rfc2616-sec14.html - Cached - Similar
HTTP/1.1: Protocol Parameters

HTTP/1.1 uses transfer-coding values in the TE **header** field (section 14.39) and

HTTP/1.1 uses entity tags in the ETag (section 14.19), **If-Match** (section ... An entity tag consists of an opaque quoted **string**, possibly prefixed by a ...

www.w3.org/Protocols/rfc2616-sec3.html - 16 hours ago - Cached - Similar

[Show more results from www.w3.org](#)
DisplayFilters - The Wireshark Wiki

Oct 20, 2008 ... The master list of display filter **protocol** fields can be found in the ... **Match** packets where SIP To-**header** contains the **string** "a1762" ...

wiki.wireshark.org/DisplayFilters - Cached - Similar
Uses of Class org.apache.abdera.protocol.client.RequestOptions ...

Methods in org.apache.abdera.**protocol**.client that return RequestOptions ... setIfMatch (**String** entity_tag) Sets the value of the HTTP **If-Match header** ...

abdera.apache.org/docs/api/.../protocol/.../RequestOptions.html - Cached - Similar
RequestOptions (Abdera Bundle Jar 0.4.0-incubating API)

Fields inherited from class org.apache.abdera.**protocol**.util. ... Create the

RequestOptions object with the specified If-None-**Match header** value public

RequestOptions setEncodedHeader(**String header**, **String** charset, **String** value) ...

abdera.apache.org/docs/api/.../protocol/.../RequestOptions.html - Cached - Similar
Network-Based Application Recognition, Cisco IOS Release 12.2(18 ...

no **match protocol** http [url url-**string** | host hostname-**string** | mime MIME-type | c-**header**-field c-**header**-field-**string** | s-**header**-field s-**header**-field-**string** ...

https://www.cisco.com/.../products_feature_guide09186a0080906451.html - Cached
RFC 2616 - Hypertext Transfer Protocol -- HTTP/1.1

HTTP allows an open-ended set of methods and **headers** that indicate the ... consisting of a structured sequence of octets **matching** the syntax Thus 2DIGIT is a 2-digit number, and 3ALPHA is a **string** of three alphabetic characters. ...

tools.ietf.org/html/rfc2616 - Cached - Similar
download - Use of Entity Tags in XMPP Extensions

Note: The ETag and If-None-**Match headers** SHOULD be used only in &IQ; ... some-new-opaque-**string** The payloads exchanged in the &xep0016; **protocol** can also be ...

xmpp.org/extensions/xep-0150.xml - Cached
FREE STRING MATCH ENCODING AND PREVIEW - Patent application ...

The user can select **protocol**, device address and free **string match** ... case" or "**match** case" or "start search for data at beginning of **protocol header**", ...

www.faqs.org/patents/app/20090187568 - Cached
Protocol Basics - Google Data Protocol - Google Code

To do a full-text search for a particular **string**, when using a service that **If-Match**: *. The following example deletes an entry (if **headers** are set ...

code.google.com/apis/gdata/docs/2.0/basics.html - Cached - Similar

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#)
[Next](#)

string exclusive OR match header Search

[Search within results](#) [Search Help](#)
[Give us feedback](#)

[Google Home](#) [Advertising Programs](#) [Business Solutions](#) [Privacy](#) [About Google](#)